

MU1503V LDMOS TRANSISTOR

Document Number: MU1503V
Preliminary Datasheet V1.1

1500MHz, 30W, 50V High Power RF LDMOS FETs

Description

The MU1503V is a 30-watt, highly rugged, unmatched LDMOS FET, designed for wide-band commercial and industrial applications at frequencies HF to 1.5 GHz.

MU1503V



- Typical Performance (On Innogration narrow band fixture with device soldered):

$V_{DD} = 50$ Volts, $I_{DQ} = 100$ mA, CW.

Frequency	Gp (dB)	P_{out} (W)	$\eta_D@P_{out}$ (%)
915 MHz	24	36	60

- Typical Performance (On Innogration narrow band fixture with device soldered):

$V_{DD} = 50$ Volts, $I_{DQ} = 100$ mA, CW.

Frequency	Gp (dB)	P_{out} (W)	$\eta_D@P_{out}$ (%)
162.5MHz	28	39	70

Features

- High Efficiency and Linear Gain Operations
- Integrated ESD Protection
- Excellent thermal stability, low HCI drift
- Large Positive and Negative Gate/Source Voltage Range for Improved Class C Operation
- Pb-free, RoHS-compliant

Suitable Applications

- 2-30MHz (HF or Short wave communication)
- 30-88MHz (Ground communication)
- 54-88MHz (TV VHF I)
- 88-108MHz (FM)
- 118 -140MHz (Avionics)
- 136-174MHz (Commercial ground communication)
- 160-230MHz (TV VHF III)
- 30-512MHz (Jammer, Ground/Air communication)
- 470-860MHz (TV UHF)
- 100kHz - 1000MHz (ISM, instrumentation)

Table 1. Maximum Ratings

Rating	Symbol	Value	Unit
Drain--Source Voltage	V_{DSS}	120	Vdc
Gate--Source Voltage	V_{GS}	-10 to +10	Vdc
Operating Voltage	V_{DD}	+55	Vdc
Storage Temperature Range	T_{stg}	-65 to +150	°C
Case Operating Temperature	T_c	+150	°C
Operating Junction Temperature	T_j	+225	°C

Table 2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction to Case $T_c = 85^\circ\text{C}$, $T_j = 200^\circ\text{C}$, DC test	$R_{\theta JC}$	0.95	°C/W

MU1503V LDMOS TRANSISTOR

Document Number: MU1503V
Preliminary Datasheet V1.1

Table 3. ESD Protection Characteristics

Test Methodology	Class
Human Body Model (per JESD22--A114)	Class 2

Table 4. Electrical Characteristics (TA = 25 °C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
DC Characteristics					
Drain-Source Voltage V _{GS} =0, I _{DS} =1.0mA	V _{(BR)DSS}		122		V
Zero Gate Voltage Drain Leakage Current (V _{DS} = 50V, V _{GS} = 0 V)	I _{DSS}	---	---	1	μA
Gate--Source Leakage Current (V _{GS} = 10 V, V _{DS} = 0 V)	I _{GSS}	---	---	1	μA
Gate Threshold Voltage (V _{DS} = 50V, I _D = 600 μA)	V _{GS(th)}	---	2.73	---	V
Gate Quiescent Voltage (V _{DD} = 50 V, I _D = 100 mA, Measured in Functional Test)	V _{GS(Q)}	---	3.57	---	V
Common Source Input Capacitance (V _{GS} = 0V, V _{DS} =50 V, f = 1 MHz)	C _{ISS}		28.3		pF
Common Source Output Capacitance (V _{GS} = 0V, V _{DS} =50 V, f = 1 MHz)	C _{OSS}		11.9		pF
Common Source Feedback Capacitance (V _{GS} = 0V, V _{DS} =50 V, f = 1 MHz)	C _{RSS}		0.38		pF



Functional Tests (In Demo Test Fixture, 50 ohm system) V_{DD} = 50 Vdc, I_{DQ} = 100mA, f = 915 MHz, CW Signal Measurements, Pin=21.5dBm

Power Gain@Pout	G _p	---	24	---	dB
Output Power	P _{out}	30	36		W
Drain Efficiency@Pout	η _D	---	60	---	%
Input Return Loss	IRL	---	-7	---	dB

TYPICAL CHARACTERISTICS

Figure 1: Pulsed CW Gain and Power Efficiency as a Function of Pout at 162.5MHz

Signal: CW Vgs=3.72V, Vds=50V, Idq=100mA



MU1503V LDMOS TRANSISTOR

Document Number: MU1503V
Preliminary Datasheet V1.1

Package Outline

Flanged ceramic package; 2 leads




Figure 1. Package Outline PKG-G2E

MU1503V LDMOS TRANSISTOR

Document Number: MU1503V
Preliminary Datasheet V1.1

Revision history

Table 5. Document revision history

Date	Revision	Datasheet Status
2017/7/18	V1.0	Preliminary Datasheet Creation
2021/1/15	V1.1	Add 162.5MHz data

Application data based on GZY-19-07

Disclaimers

Specifications are subject to change without notice. Innogration believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Innogration for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Innogration. Innogration makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Innogration in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Innogration products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Innogration product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility. For any concerns or questions related to terms or conditions, pls check with Innogration and authorized distributors

Copyright © by Innogration (Suzhou) Co.,Ltd.