




GaN HEMT 50V, 280W, 1.8-2.2GHz RF Power Transistor

Description

The STBV22280BY4 is a dual path 280watt , Input matched GaN HEMT, ideal for applications from 1.8 to 2.2GHz especially for LTE/5G

There is no guarantee of performance when this part is used outside of stated frequencies.

- Typical WCDMA 1 carrier performance on 2.1GHz asymmetrical Doherty with device soldered VDS= 48V, IDQ=150mA(Vgm=-3.3V, Vgp=-5.50V)



Freq (MHz)	Pout (dBm)	CCDF (dB)	Ppeak (dBm)	Ppeak (W)	ACPR (dBc)	Gain (dB)	Eff (%)
2110	46.50	9.01	55.52	356.5	-27.3	14.8	59.6
2140	46.50	8.87	55.37	344.2	-26.9	14.7	59.2
2170	46.50	8.39	54.90	308.7	-28.1	14.5	58.3

Applications

- Asymmetrical Doherty amplifier within 1.8-2.2GHz
- Sub-2GHz power amplifier
- CW or pulsed Amplifier

Important Note: Proper Biasing Sequence for GaN HEMT Transistors

Turning the device ON

1. Set VGS to the pinch--off (VP) voltage, typically -5 V
2. Turn on VDS to nominal supply voltage
3. Increase VGS until IDS current is attained
4. Apply RF input power to desired level

Turning the device OFF

1. Turn RF power off
2. Reduce VGS down to VP, typically -5 V
3. Reduce VDS down to 0 V
4. Turn off VGS

Figure 1: Pin Connection definition

Transparent top view (Backside grounding for source)




Table 1. Maximum Ratings

Rating	Symbol	Value	Unit
Drain--Source Voltage	V _{DSS}	+200	Vdc
Gate--Source Voltage	V _{GS}	-8 to +0.5	Vdc
Operating Voltage	V _{DD}	55	Vdc



Maximum gate current	I _{gs}	40.2	mA
Storage Temperature Range	T _{stg}	-65 to +150	°C
Case Operating Temperature	T _c	+150	°C
Operating Junction Temperature	T _j	+225	°C

Table 2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction to Case by FEA T _c = 85°C, at Pd=40W, on Doherty application board	R _{θJC}	2.2	°C /W

Table 3. Electrical Characteristics (TA = 25°C unless otherwise noted)

DC Characteristics (Main path, measured on wafer prior to packaging)

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{GS} =-8V; I _{DS} =15mA	V _{DSS}		200		V
Gate Threshold Voltage	V _{DS} =10V, I _D = 15mA	V _{GS(th)}	-4		-2	V
Gate Quiescent Voltage	V _{DS} =50V, I _{DS} =150mA, Measured in Functional Test	V _{GS(Q)}		-3.3		V

DC Characteristics (Peak path, measured on wafer prior to packaging)

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{GS} =-8V; I _{DS} =25.2mA	V _{DSS}		200		V
Gate Threshold Voltage	V _{DS} =10V, I _D = 25.2mA	V _{GS(th)}	-4		-2	V
Gate Quiescent Voltage	V _{DS} =50V, I _{DS} =150mA, Measured in Functional Test	V _{GS(Q)}		-3.4		V

Ruggedness Characteristics

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Load mismatch capability	2.14GHz, P _{out} =45W WCDMA 1 Carrier in Doherty circuit All phase, No device damages	VSWR		10:1		

Figure 2: Median Lifetime vs. Channel Temperature






Figure 3: Efficiency and power gain as function of Pout (2.1-2.2GHz Doherty)




Figure 4: Network analyzer output, S11 and S21 (2.1-2.2GHz Doherty)




Figure 5: Picture of application board Doherty circuit for 2.1-2.2GHz





Table 4. Bill of materials of application board (PCB layout upon request, RO4350B 20mils)

Designator	Footprint	Comment	Quantity
C1, C2, C4, C5, C6, C7, C8	0603	18pF	7
C3	0603	3.3 pF	1
C9, C10, C11, C12	1210	10uF/100V	4
C13, C14		100uF/63V	2
R1,R2	0603	10R	2
R3	2512	51R	1
W1*		HPK2F	1



Earless Flanged Ceramic Package; 4 leads



UNIT	A	b	c	D	D ₁	e	E	E ₁	F	H	H ₁	L	Q	U ₁	U ₂	W ₁	W ₂
mm	4.72	4.67	0.15	20.02	19.96	7.90	9.50	9.53	1.14	19.94	12.98	5.33	1.70	20.70	9.91	0.25	0.51
	3.43	4.93	0.08	19.61	19.66		9.30	9.25	0.89	18.92	12.73	4.32	1.45	20.45	9.65		
inches	0.186	0.194	0.006	0.788	0.786	0.311	0.374	0.375	0.045	0.785	0.511	0.210	0.067	0.815	0.390	0.01	0.02
	0.135	0.184	0.003	0.772	0.774		0.366	0.364	0.035	0.745	0.501	0.170	0.057	0.805	0.380		

OUTLINE VERSION	REFERENCE			EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA		
PKG-B4					03/12/2013



Revision history

Table 4. Document revision history

Date	Revision	Datasheet Status
2022/7/26	V1.0	Preliminary Datasheet Creation

Application data based on: LSM-22-10

Notice

Specifications are subject to change without notice. Innegration believes the information within the data sheet to be reliable. Innegration makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose.

“Typical” parameter is the average values expected by Innegration in quantities and are provided for information purposes only. It can and do vary in different applications and related performance can vary over time. All parameters should be validated by customer’s technical experts for each application.

Innegration products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Innegration product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.

For any concerns or questions related to terms or conditions, please check with Innegration and authorized distributors

Copyright © by Innegration (Suzhou) Co.,Ltd.