




GaN HEMT 28V, 2450MHz 60W, RF Power Transistor

Description

The XTAH25060A2C is a 60W GaN HEMT, designed for ISM/RF Energy application at 2.45GHz. It can be used in CW, Pulse and any other modulation modes. There is no guarantee of performance when this part is used in applications designed outside of these frequencies.

- Typical 2.4-2.5GHz full band class AB RF Performance with device soldered
 $V_{DS}=28V$, $V_{GS}=-3V$



Voltage(V)	Pin(dBm)	Psat(W)	Gain(dB)	Eff(%)
28	33	63-66	15~15.2	74-76
32	33	77-81	15.9~16.1	72-73

Recommended driver: ITEH40004P3 or GTAH80004PD

Applications

- S band power amplifier
- ISM/RF Energy power amplifier

Important Note: Proper Biasing Sequence for GaN HEMT Transistors

Turning the device ON

1. Set VGS to the pinch-off (VP) voltage, typically -5 V
2. Turn on VDS to nominal supply voltage
3. Increase VGS until IDS current is attained
4. Apply RF input power to desired level

Turning the device OFF

1. Turn RF power off
2. Reduce VGS down to VP, typically -5 V
3. Reduce VDS down to 0 V
4. Turn off VGS

Table 1. Maximum Ratings

Rating	Symbol	Value	Unit
Drain--Source Voltage	V_{DSS}	+150	Vdc
Gate--Source Voltage	V_{GS}	-8 to +0.5	Vdc
Operating Voltage	V_{DD}	36	Vdc
Maximum gate current	I_{GS}	18	mA
Storage Temperature Range	T_{stg}	-65 to +150	°C
Case Operating Temperature	T_C	+150	°C
Operating Junction Temperature	T_J	+225	°C

Table 2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction to Case by FEA $T_C=85^{\circ}C$, at $P_{diss}=25W$	$R_{\theta JC}$	3.2	°C /W

Table 3. Electrical Characteristics (TA = 25°C unless otherwise noted)

DC Characteristics (measured on wafer prior to packaging)


Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{GS}=-8V$; $I_{DS}=13.6mA$	V_{DSS}		150		V
Gate Threshold Voltage	$V_{DS}=10V$, $I_D=13.6mA$	$V_{GS(th)}$	-4		-2	V
Gate Quiescent Voltage	$V_{DS}=28V$, $I_{DS}=200mA$, Measured in Functional Test	$V_{GS(Q)}$		-2.27		V



Ruggedness Characteristics

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Load mismatch capability	2.5GHz, Pout=60W Pulsed CW All phase, No device damages	VSWR		10:1		

Figure 2: Median Lifetime vs. Channel Temperature



Typical performance

Figure 5: Network analyzer output S11/S21




Figure 5: Picture of application board






Table 4. Bill of materials of application board (PCB layout upon request)

Component	Description	Suggestion
C0	470uF/63V	Electrolytic Capacitor
C1, C2, C3	10uF	1210
C4, C5, C7	15pF	Beijing YuanLu HongYuan Electronic Technology CO., LTD MQ400805
C6	3.9pF	Beijing YuanLu HongYuan Electronic Technology CO., LTD MQ400805
R1	Chip Resistor, 10Ω	0805
PCB	Rogers 4350b, thickness 20 mils, 1oz copper	



Package Dimensions (Unit:mm)



Unit:mm

Tolerance ± 0.10 mm, Except as Noted.

Revision history

Table 4. Document revision history

Date	Revision	Datasheet Status
2025/1/23	V1.0	Preliminary Datasheet Creation

Application data based on: RXT-25-01

Notice

Specifications are subject to change without notice. Innegration believes the information within the data sheet to be reliable. Innegration makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose.

“Typical” parameter is the average values expected by Innegration in quantities and are provided for information purposes only. It can and do vary in different applications and related performance can vary over time. All parameters should be validated by customer’s technical experts for each application.

Innegration products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Innegration product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.

For any concerns or questions related to terms or conditions, please check with Innegration and authorized distributors

Copyright © by Innegration (Suzhou) Co.,Ltd.